

ST-E 44 EVO S&F

Water-based Sublimation ink
for transfer printing specific for Sport & Fashion



Sublimation Textile



TECHNICAL DATA SHEET

isonik

ST-E 44 EVO S&F

Water-based Sublimation ink for transfer printing specific for Sport & Fashion



EPSON



SPECIFIC FOR FASHION



SPORTSWEAR SPORTS EQUIPMENT



HIGH DYE CONCENTRATION



TRANSFER PRINTING



FOR COATED AND UNCOATED PAPER



BRIGHT AND VIBRANT COLOURS



STORAGE CONDITIONS:
AT 5-30°C
TEMPERATURE
DRY AND WELL-VENTILATED ENVIRONMENT



PRINTING CONDITIONS:
20-25°C
TEMPERATURE
40-60%RH
HUMIDITY RANGE



SEA FREIGHT SHIPMENT CONDITIONS
5-30°C
TEMPERATURE
REFRIGERATED CONTAINER FOR LONG DISTANCE



AVAILABLE PACKAGING
1 KG BOTTLE AND 5 KG TANK



TRANSFER CONDITIONS
200-210°C
FOR 35-45 SEC



HEAT-SENSITIVE PRODUCT
DO NOT EXCEED 30°C
AVOID DIRECT SUNLIGHT



Product description

ISONIK® ST-E 44 EVO S&F is a water-based digital sublimation ink for transfer printing. It is suitable for most of the printers available on the market equipped with Epson technology print heads of different generation. The high dye concentration and innovative formulation make this series the most suitable choice for printing particularly critical substrates, where extreme drying speeds and high colour yields are the minimum requirements for outstanding prints.

ISONIK ST-E 44 EVO S&F is suitable for 100% polyester fabrics or in blends with different fibers with minimum of 70% of PES. It can be used also on any substrate (alu, wood, ceramic, glass, etc.) usually unsuitable for sublimation process, after pretreating with polyester-polyamide resins.

Instructions

- ISONIK ST-E 44 EVO S&F is ready to use.
- Keep ISONIK ST-E 44 EVO S&F at printing room temperature at least 24 h before use.
- Shake gently before use.
- Follow instructions on label and MSDS.
- Transfer conditions by using a calender or a flat press: temperature 200-210°C for 35/45 sec.
- Care about correct and regular printer maintenance.
- Preliminary tests are recommended to set the best operating parameters (T°C / t sec) to achieve the desired result. Product performance might vary according to the employed hardware, software and the applied printing method.

Notes

- Information regarding fastness and additional technical features available upon specific request
- Customized colours available upon request



DISCLAIMER

The information included in this document is based on experience and the current state of our knowledge and is not intended to be completely exhaustive. The product is for professional use only. Due to multiple factors that could influence the application aspects of ISONIK ST-E 44 EVO S&F and thus the final result obtained, Isocarbo suggests to always carry out preliminary tests in order to evaluate possible abnormal behaviour of the products under particular operating conditions different from those stated in this document. Therefore, Isocarbo assumes no responsibility for any differences in the performance of ISONIK ST-E 44 EVO S&F and for any loss or damage suffered by persons or property as a result of the information contained in this document. Furthermore, Isocarbo accepts no responsibility for any damage caused to third parties as a result of improper use of ISONIK ST-E 44 EVO S&F by any person or company. Isocarbo assures its commitment to the continuous development and improvement of the product and assumes the right to change and update the contents of this technical document at any time.



www.isocarbo.it

isocarbo

Via per Albate, 4
22070 Senna Comasco (CO) Italy
Ph +39 031 507307
info@isocarbo.it

Made in Italy

